


Millimetre-Wave Radio

MMW Radio—60 & 70/80GHz
Gigabit Ethernet



About Millimetre-Wave

MMW (Millimetre Wave) links offer higher performance connections using high frequency microwave technology offering bandwidths of up to 1.5Gbps Full Duplex capacity. MMW technology is complimentary to FSO (Free Space Optics) and ideal for dense urban areas where radio spectrum is congested. Planning for MMW is based on rainfall, giving useful transmission distances of many kilometres.



System Features

- Capacity 1.25Gbps Full Duplex
- Versions for unlicensed 60GHz and semi-licensed 70/80GHz bands
- Range from 1.5 up to 20km*
- “Pencil beams” of 0.5 - 0.8degrees
- Rugged outdoor grade waterproof enclosure

Applications

- 4G/LTE Backhaul Infrastructure
- Wireless Internet Service Providers (WISP)
- Point-to-Point Wireless networking
- Corporate backbone or Telecom service provider
- Resilience for FSO or Fibre links
- Fast Roll-out & Temporary Deployment

*Depends on environment and antennas

Product Features and Benefits

CableFree MMW products are highly robust and ruggedized for operation in harsh climates.

The highly integrated Full-Outdoor radio units are shipped with a choice of 30cm or 60cm antennas to meet customer network requirements.

Inside the radio unit there are connectors for user network interface and power. The default network interface is 10/100/1000BaseT with RJ45 connector, and an SFP feature for optional SFP optical interface for Multimode or Singlemode fibre interface with LC fibre optic connectors. Various choices of SFP area available to match customer network equipment and fibre installations.

The links are supplied with mounting brackets to mount the units on poles which are typically installed on walls, towers or roof top locations to ensure clear Line of Sight (LOS) between the end points of the wireless link.

Alignment of the links is achieved using simple Digital Voltmeter connection to the radio unit as common with most microwave links and takes a skilled installer team typically 5-20 minutes.

When installed the links provide “fit and forget” connectivity between the nodes on the network and can be remotely managed and monitored using a choice of Web-based NMS and SNMP Management platforms.

Gigabit Ethernet using 57-64/55-66 & 71-76/81-86 GHz Millimetre Waves

The CableFree range of high performance radios use millimetre wave frequencies. Using high frequency microwave signals at 60GHz and above, large bandwidths of up to Full Duplex Gigabit Ethernet capacity can be provided.

Millimetre wave is a technology complimentary to FSO (Free Space Optical) communication systems. Planning for Millimetre wave is based on rainfall, compared to FSO which is based on visibility, predominantly fog.

CableFree MMW-60-GE and MMW-70-GE are full-duplex Gigabit point-to-point links especially designed according to FCC and ETSI requirements. They provides interconnection between remote LAN segments at ultra-high speed and utilizes Gigabit Ethernet protocols, which is the evolving standard for switches and routers available from a variety of telecommunication equipment manufacturers.

One full-duplex Gigabit Ethernet link provides 1.25 gigabit-per-second connectivity that is the equivalent of approximately 650 T1 lines or 1,000 DSL connections. The MMW-70-GE product has 10/100/1000Base T and optional 1000 Base-SX fibre optic connections at each end of the wireless link and operates as a transparent link. The resulting connection can replace a fibre-optics cable physically connected end-to-end. The wireless millimetre wave Gigabit link provides fibre equivalent performance, reliability and security but with no high deployment cost associated with outdoor fibre installations.

The Gigabit Ethernet point-to-point millimetre wave radio links have been designed with compact parabolic Cassegrain antennas of 30 and 60 cm diameters, with narrow beam widths of 0.4 and 0.9 degrees which maximises signal margin across the link and ensures lack of interference from other links or sources.

The MMW-70-GE operating distances vary from 1.5 to 20 km for varying weather conditions depending of the link frequency and rain intensity. Planning for millimetre wave spectrum use must take into account the propagation characteristics of radio signals at this frequency range. While signals at lower frequency bands can propagate for many miles and penetrate more easily through buildings, millimetre wave signals can travel only a few miles or less. However, these characteristics of millimetre wave propagation are not necessarily disadvantageous. Millimetre waves can permit more densely packed communications links, thus providing very efficient spectrum utilization, and they can increase security of communication transmissions.

Specifications

System Variant	MMW-70/80-GE	MMW-60-GE
System Parameters		
Frequency Band	E band	60GHz band
Bandwidth	71-76 GHz & 81-86GHz	57-64 (FCC) or 59-66 (TELEC) GHz
Capacity	1250 Mbps Full duplex	1250 Mbps Full duplex
Modulation Type	ASK	ASK
Rx Sensitivity	-59 dBm (@ BER 1E-12 or error free)	-59 dBm (@ BER 1E-12 or error free)
Output Power	23dBm (200 mW)	10 mW
Forward Error Correction (FEC)	RS(255, 239) Optional Feature	RS(255, 239) Optional Feature
Network Management	Web based NMS, SNMP Features	Web based NMS, SNMP Features
Data and Aux Interface		
Ethernet Interface	10/100/1000BaseT RJ45, Optional SFP for 1000Base-LX/SX (singlemode & multimode fiber)	10/100/1000BaseT RJ45, Optional SFP for 1000Base-LX/SX (singlemode & multimode fiber)
Diagnostics Port	RS-485 [with optional RS-232]	RS-485 [with optional RS-232]
Antenna		
Antenna Type	Cassegrain type antenna with radome	Cassegrain type antenna with radome
Antenna Gain/ beamwidth 60 cm	30cm: 45dBi, 0.9° beamwidth 60cm: 51dBi, 0.5° beamwidth	30cm: 42dBi, 1.2° beamwidth 60cm: 47dBi, 0.5° beamwidth
Power / Environment		
Power Supply AC	Input 88-264 Volts, 50/60 Hz	Input 88-264 Volts, 50/60 Hz
Power Consumption	20 W maximum	20 W maximum
DC Power	36 to 72 Volts DC, external AC supply option	36 to 72 Volts DC, external AC supply option
Power Connector Ethernet /	Internal connectors for Power and Ethernet	Internal connectors for Power and Ethernet
Operational Temperature	-30°C to +70°C	-30°C to +70°C
Humidity	0 to 95%, non-condensing	0 to 95%, non-condensing
Physical Dimensions		
Outdoor unit size w/o antenna	330 x 350 x 460 mm	330 x 350 x 460 mm
Weight (with ant, no bracket)	30cm: 1 kg (inc. antenna, no bracket) 60cm: 5kg (inc. antenna, no bracket)	30cm: 1 kg (inc. antenna, no bracket) 60cm: 5kg (inc. antenna, no bracket)

Product Code

Product Code	Description
CFMMW-70/80-GE-xx	70/80GHz E-band MMW Gigabit Ethernet radio including IP65-rated outdoor unit, management software, Power supplies with mains 115/230Vac input. Does not include Ethernet cables.
CFMMW-60-GE-xx	60GHz MMW Gigabit Ethernet radio including IP65-rated outdoor unit, management software, Power supplies with mains 115/230Vac input. Does not include Ethernet cables.
Options: -30 or -60	Antenna sizes 30 or 60cm